

LM3800TX DC JACKSHAFT DOOR OPENER

Maintenance-free, Jackshaft DC motor for smooth operation.



KEY FEATURES

- HEAVY-DUTY**
DC motor with automatic force sensing
- LIFTING**
For doors up to 130 kg
- SPACE-SAVING**
Design maximizes versatility



SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

SOFT-START AND SOFT-STOP FOR SMOOTH OPERATION.

INCLUDED AUTOMATIC GARAGE DOOR LOCK MAKES THE GARAGE DOOR VIRTUALLY IMPENETRABLE.

QUIET AND RELIABLE

QUIET DC MOTOR ELIMINATES NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

HEAVY LIFTING POWER OPERATES DOORS UP TO 130 KG.

WARRANTY MOTOR: 2 YEARS, ACCESSORIES: 2 YEARS.

SECURE & SAFE

AUTOMATIC GARAGE DOOR OPENERS IMPEDE UNAUTHORIZED ACCESS TO THE GARAGE.

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

EVOLUTION RADIO (SECURITY+ 2.0®) SENDS A NEW CODE WITH EVERY REMOTE CLICK.

AUTOMATIC FORCE SETTING & OBSTACLE DETECTION.

INCLUDED ACCESSORIES:

TWO 4-CHANNEL UNIVERSAL REMOTE CONTROL
Operates up to 4 openers. Compact to provide quick, easy garage access.



TX4UNIS

COLLAR
Ensures safe connection between the shaft and the opener.



E-LOCK
Deadbolts the garage door automatically every time it closes.



CABLE TENSION MONITOR
Increases safety and helps to prevent door from falling. Incl. cable.



POWERFUL ADD-ONS:

BATTERY BACK-UP
Battery status via LED
Ready for plug in, 24 V.
80 cm cable.



CM475

WIRELESS KEYPAD
Provides convenient, secure access from outside the garage with a 4-digit PIN.



9747E

FAILSAFE SAFETY SENSOR
2-wire system with LiftMaster signal
IP44, range 15 meters.



772E

LM3800TX 40Nm
DC DIRECT DRIVE „JACKSHAFT“
FOR DOORS UP TO 130 KG

40 Nm

MASTERFUL ENGINEERING.

DC DIRECT DRIVE „JACKSHAFT”
FOR DOORS UP TO 130 KG.

MOTOR



- Heavy-Duty 24 V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Operating Temperature: -30°C to 50°C

POWER



- 230-240 V AC
- 50 Hz Voltage
- 5 W Stand-by Power
- 90 cm Power Cord

MECHANICS




- High Quality Chassis and Cover
- Reliable & Powerful Direct drive „Jackshaft”
- Automatic Force Setting
- Electronic Limits for Easy Setup
- Clutch unlatch for manual operation



STANDARD SPECS.

SECURE

EVOLUTION RADIO (Security+ 2.0®)



- 4-Button Remote Control (TX4UNIS)
- Remote Control: 433 MHz Tri-Band¹
- Jackshaft Door Opener: Frequency Agile on 433 MHz
- Copy-Protected Coding

SMART

RADIO



- Communication from jackshaft door opener and accessories.
- Receiver with 64 memory registers.

HOMELINK® COMPATIBLE
(VERSION V OR SOFTWARE REV. 8)²

36 rpm

Rounds per minute for door to move upward

SPEED

24 rpm

Rounds per minute for door to move downward

SHIPPING.

SHIPPING WEIGHT
(in kg)



CARTON

CARTON: 60.7 cm x 26.1 cm x 30 cm

- Jackshaft Door Opener (40Nm)
- Two 4-Button Remote Control (TX4UNIS)
- Collar, E-Lock and Cable Tension Monitor

SAFETY AND SECURITY.



- External Quick Release (optional)
- Down Safety Reverse
- Up Safety Stop
- Automatic Obstacle Detection
- Soft-Start / Soft-Stop
- Timer to Close (automatic close) Programming (when safety sensors connected)

¹Tri-band on EVOLUTION Radio (Security+ 2.0®) coding only. TX4UNIS remote control is backwards compatible to all LiftMaster openers manufactured since 1997 with 433 MHz.

²May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.